



THE GERBERCUTTER® DCS 1500
IS A COMPACT, HIGH-SPEED,
SINGLE- OR LOW-PLY, STATIC TABLE
CUTTING SYSTEM, DESIGNED TO
CUT A WIDE VARIETY OF MATERIALS.
THE SYSTEM IS MOST SUITED TO
CUTTING SAMPLES, PROTOTYPES,
OR SHORT PRODUCTION RUNS. ITS
CUTTING ACCURACY IS MEASURED
IN MILLIMETERS AND IT CUTS AT
SPEEDS UP TO 1.1 METERS PER
SECOND (45 INCHES PER SECOND).

Get accurately cut parts every time.

- The DCS 1500 employs a powerful vacuum system to hold material firmly in place during cutting to ensure quality cut parts.
- Adjust pressure on the cutting tools to cut a wide variety of materials with precision.
- The cutting head is designed to accommodate three tools simultaneously to minimize tool changes. Choose from multiple types of straight knives, wheel knives, notching tools and punches. Includes a pen for annotation. Disposable blades are inexpensive and easy to change.

Easy to use.

- Because the DCS 1500 is highly intuitive, migration from manual cutting is easy. It is typically installed in one day.
- Windows®-based software employs a graphical user interface to simplify operator training and daily use.
 Includes wizards to automate repetitive processes and speed preparation of the cutting job.

- Easily stores cutting setup files for quick retrieval to accelerate future cut jobs.
- The DCS 1500 is network-compatible for easy transfer of data from a wide variety of CAD systems.

Realize a fast return on your investment.

- Automatic end cutting eliminates material waste by cutting precisely at the end of each marker.
- Single-ply cutting enables you to cut to order. Reduce work in process, lead times and work planning.
- The optional Toolpath module in CutWorks® software optimizes cut times by sequencing parts (and internal cuts) in the most efficient order for cutting. Automatically removes common lines between parts to achieve zero buffer cutting.
- No paper underlay or plastic overlay required for most materials.
- The DCS 1500's small footprint minimizes floor space requirements.


GERBER DCS 1500 CUTTER



The easy-to-use keypad controls many machine functions at the cutter.



Use up to three cutting tools and a pen on the head assembly for maximum flexibility.



CutWorks software offers a complete design, nesting and cutting solution.

Gerber Technology 24 Industrial Park Road West Tolland, CT 06084 USA

TOLL FREE (USA) 800.826.3243

TELEPHONE (International) +1.860.871.8082

www.gerbertechnology.com


Form No. 05192017

Available Options & Services

- Complete service and parts supply packages
- Training for operators, technicians and applications personnel is available
- Porous or drilled plastic cutting surface
- Large wheel package with 44.5 mm (1.75") diameter wheel to cut lofty materials
- Nesting Video Projector: Project parts onto material to enable manual adjustments



ZipJet[™], inkjet part identification system



InfoJet[™] inkjet labeling system offers fast, accurate identification of cut parts with visible and UV inks



V-notch and punch tools are available for additional cutting capability

Technical Specifications

| Characteristics | | |
|--------------------------|--|----------------------------------|
| Fabric Height | Single Ply | |
| Cutting Speed (maximum) | 1,1 m/second | 45 in./second |
| Machine Dimensions | 2,44 x 2,03 m 2,44 x 2,36 m | 96 x 80 in. 96 x 93 in. |
| Cutting Area | 1,52 x 1,47 m 1,52 x 1,80 m | 60 x 57.77 in. 60 x 70.77 in. |
| Table heights | 0,84 or 0,86 m | 33 or 34 in. |
| Electrical Requirements | | |
| Control and Drive System | 110V @ 20 amps or 220V @ 10 amps, single phase | |
| Table Vacuum | Single phase 220V 50Hz 16A rated/112A start up Single phase 115V 60Hz 29A rated/172A start up Single phase 208/230V 60Hz - 15A rated/95-86A start up | |
| | | |
| | | |
| Compressed Air | 5,5 - 8,3 bar @ 14 liters/min (80 - 120 PSI @ 0.5 SCFM) | |
| Operating Environment | | |
| Temperature (maximum) | 43°C | 110°F |
| Humidity (maximum) | 95% (non-condensing) | |
| Vacuum System | 760 m above sea level | 2,500 ft. above sea level |

NOTE: Configurations vary according to options selected. Specifications are subject to change without notice.

GERBERcutter, ZipJet, InfoJet and CutWorks are trademarks or registered trademarks of Gerber Technology LLC. Windows is a registered trademark of Microsoft Corporation.

